

IHRESS

PREMIUM PACKAGING MACHINERY



iFCM-A3F

Semi-automatic strapping machine




Pol. Ind. Can Turull - Naves 8 y 9
Carretera c-1413a Km. 35 | 08181 Sentmenat (ESPAÑA)
+34 936 555 600 | ihress.com | info@ihress.com

Technical Features

- Working table with safety sensor
- Electronic strapping tensioning
- Robust strapping head
- Possibility to work with different strap sizes
- Motors only work during the strapping cycles
- Strapping group with dc motors
- Analog control panel
- Minimum tensioning only 3 kg
- Maximum tensioning up to 45 kg
- Four pivoting wheels, two of them with brake
- Adjustable cooling time
- Adjustable strapping tensioning by potentiometer
- Adjustable sealing blade temperature
- Adjustable strap feeding length



Control Panel



Strapping head details

Data Sheet

Power supply	220 V 1 ph 50/60 Hz 0,25 kW
Machine dimension	L 850 x W 555 x H 750-900 mm
Working table height	750 - 900 mm
Strapping speed	10/15 ciclos/min
Tension strength	3 - 45 KG
Net machine weight (Kg)	65 KG

Product Features

Min. Product dimensions	L 80 x W 80 x H 3 mm
Max product weight	25 KG

Strap Roll Features

Internal diameter	200 mm.
External diameter	400 - 500 mm.
Coil width	190 mm.
Strap width	6 - 9 - 12 - 15 mm.
Strap thickness	0,5 - 0,7 mm.
Strap type	PP/PET

STANDARD MACHINE DIMENSIONS

