

IHRESS

PREMIUM PACKAGING MACHINERY



iP15UD

***Semiautomatic single format case sealer
with upper and lower conveyor belt***



Pol. Ind. La Serra
C. Camí de la caseta, 3-6 | 08185 Lliçà de Vall (BARCELONA)
+34 936 555 600 | ihress.com | info@ihress.com

STANDARD TECHNICAL FEATURES

- Drag of boxes using bands with independent motors placed in the upper and lower positions.
- Top and bottom carton sealing.
- Weight 140 Kg.
- Adjustable working height from 570 mm to 800 mm
- Adjustable tape tension.
- Interchangeable taping head which allows using tape from 48 mm to 72 mm width.
- Metal rollers for the transportation of carton.
- Adjustable top guides to keep flaps squared while sealing.
- Hand wheel adjustment of carton width and height.
- Emergency stop on top taping head for quick access.

Carton dimensions

- Type: RSC o B1
- Length: 100 – ∞ mm
- Width: 150 – 570 mm
- Height: 120 - 490 mm

The quality and format of the cases must be verified and approved by the IHRESS technical office

Taping head



SPECIAL OPTIONS

Infeed/outfeed free rollers



Extensible free wheels outfeed conveyor from 1,2 m to 4,8 m



| Technical features | Standard |
|---|---------------------------------------|
| Electric power: | 220 V 50 Hz Single phase |
| Installed power: | 0,45 Kw |
| Belts speed: | 20 m/min. |
| Top and bottom carton sealing | Tape (48 a 72 mm) |
| Dimensional adjustment: | Manual |
| Production (variable depending on format): | Depending on carton format & operator |
| Other components on request it can add an extra cost. | |

| Options |
|---|
| Stainless Steel AISI 304 |
| 3-flaps folder (just in model P15) |
| Flap Holder (for bottom flaps) |
| Infeed/outfeed free rollers conveyor 500 mm lenght |
| Infeed/outfeed free rollers conveyor 1.000 mm lenght |
| Extensible free wheels outfeed conveyor from 1,2 m to 4,8 m |
| Extensible conveyor conector. |
| Possibility of "machine on demand" with special dimensions |
| Possibility of models with upper and lower engines |
| Other colors on request (it can add an extra cost) |



iP15UD Detail



iP15UD

STANDARD MACHINE LAYOUT

